

Non-Automated
Minibars



THE
SMARTCUBE[®]
CLASSIC COLLECTION
(non-automated)



MINIBAR SYSTEMS
smart bars • smart people • smart solutions



Classic 60 solid foam glass door

SmartCube Classic - Engineered to upgrade in the future

SmartCube Classic minibars have been quality engineered with generous internal space, simple and stylish design, low energy consumption and silent thermoelectric cooling technology. It's a great value for your hotel.



Classic 40 glass door



Classic 40 solid door



Classic 42d drawer minibar

Quality Engineered

- 30% more energy efficient over previous models
- Environmentally sustainable energy efficient cooling system
- Peltier Thermoelectric Superconductor 5 Heat Pipe technology
- State-of-the-art insulation properties (Argon, low-E glass)
- Solid foam insulated frame for glass door
- Magnetic seals to keep the door tightly closed
- Free of hazardous materials
- Cyclopentane foaming agent – most environmentally friendly material
- Automatic defrost

Upgradable Design

- Classic Honor Bar -> Door Open -> Fully Automated
- Maximum Flexibility

Technical Specifications

	Classic 40	Classic 60	Classic 42d
Capacity (liters / cubic feet)	40 / 1.41	50 / 1.766	40 / 1.22
Dimensions HxWxD (inches) HxWxD (mm)	22.92 x 16.14 x 18.7* 582.4 x 410 x 475*	22.92 x 19.29 x 18.7* 582.4 x 490 x 475*	16.81 x 21.65 x 20.47* 427 x 550 x 520*
Door Options	Full Glass Front: No Window, Full Window, Partial Window, Stainless Full Window Solid Laminated: Black Solid, Stainless Steel		Solid Drawer
Door Hinge	Reversible	Reversible	Drawer
Shelves Type	Tempered Glass	Tempered Glass	N/A
Watts (W)	60W	42-52W	42-52W
Voltage (V)	110V / 60Hz 220V / 50Hz	110V / 60Hz 220V / 50Hz	110V / 60Hz 220V / 50Hz
Amps	0.5-0.9	0.35-0.75	0.35-0.75
Consumption (kWh/24h)**	0.43 kWh/24h**	0.32 kWh/24h**	0.32 kWh/24h**
Net Weight (lbs / kgs)	46.5 lbs / 21.1 kgs	52.91 lbs / 24 kgs	52.91 lbs / 24 kgs
Noise Level (dB)	40 dB	40 dB	40 dB
Certification	CCC/CB/CETL/CE/GS/RoHS/UL/CSA/ISO 9001 2008/ISO 14001 2004		

* Measured to door handle

**Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature, in compliance with EN ISO 7371

Specifications may change without notice due to continuous product development.

Sophisticated Design

- Translucent racking on door for high visibility of products
- Internal LED lighting
- High impact exterior finish
- Full Glass Face Door Options: no, partial or full window
- Solid Laminated Door Options: black solid, stainless steel
- Custom: stainless steel full window

Full Glass Door Options



Solid Laminated Door Options

