



### 1. Standard Features

- Environmentally sustainable energy efficient thermoelectric cooling system
- Translucent racking on door for high visibility of products
- 30% more energy efficient over previous models
- State-of-the-art insulation properties (Argon, low-E glass)
- Cyclopentane thermal foaming insulation (reduces ozone depletion)
- Reversible door hinging
- Magnetically sealed doors
- Internal LED lighting
- Automatic defrost
- ADA compliant

### 2. Upgradable Design

- Classic Honor Bar -> Door Open -> Fully Automated
- Maximum Flexibility
- Customized front panel to integrate with design†
- Case good cabinet door sliders available

### 3. Technical Specifications

	Classic LP60T Thermoelectric
Part Number	LP60T
Cooling Type	Peltier Thermoelectric Superconductor 5 Heat Pipe
Capacity (liters / cubic feet)	50 / 1.766
Dimensions HxWxD (inches)* HxWxD (mm)*	22.92 x 19.29 x 18.7* 582.4 x 490 x 475*
Door Option	Full Glass Front: No Window, Full Window, Partial Window, Stainless Full Window Solid Laminated: Black Solid, Stainless Steel
Watts (W)	42-52W
Voltage (V)	110V / 60Hz or 220V / 50Hz
Amps	0.35-0.75
Energy Consumption (kWh/24h)**	0.32 kWh/24h**
Net Weight (lbs / kgs)	52.91lbs / 24kgs
Noise Level (dB)	40 dB
Certification	CSA/CE/FCC/ETL/WEEE/RoHS ISO 9001 and ISO 14001 certified

### Full Glass Door Options



Customized silkscreening available including logo's

### Solid Laminated Door Options



\* Measured to door handle

\*\*Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature, in compliance with EN ISO 7371

† Recommended weight of panel is no more than 9 lbs. (4.08Kg). Recommended thickness, ¾ inches (18-20mm)

Specifications may change without notice due to continuous product development.