



1. Standard Features

- Environmentally sustainable energy efficient thermoelectric cooling system
- Console Box (control module) can be serviced easily and located remotely
- Shelves use infrared sensors (no moving or mechanical parts)
- Plug-and-play cold cube shelving and door racks (no cables)
- NEW robust electronic lock with mechanical override feature
- Removable product dividers for easy cleaning
- Cyclopentane thermal foaming insulation (reduces ozone depletion)
- Reversible door hinging
- Magnetically sealed doors
- Internal LED lighting
- Automatic defrost
- Self-diagnostic reporting software
- Customized front panel to integrate with design†
- Case good cabinet door sliders available
- ADA compliant

2. Technical Specifications

| | SC60T Thermoelectric |
|---|--|
| Part Number | SC60T |
| Cooling Type | Peltier Thermoelectric Superconductor 5 Heat Pipe |
| Capacity (liters / cubic feet) | 50 / 1.766 |
| Dimensions HxWxD (inches)* HxWxD (mm)* | 22.92 x 19.29 x 18.7* 582.4 x 490 x 475* |
| Door Option | Full Glass Front: No Window, Full Window, Partial Window, Stainless Full Window Solid Laminated: Black Solid, Stainless Steel |
| Watts (W) | 42-52W |
| Voltage (V) | 110V / 60Hz or 220V / 50Hz |
| Amps | 0.35-0.75 |
| Energy Consumption (kWh/24h)** | 0.32 kWh/24h** |
| Net Weight (lbs / kgs) | 52.91lbs / 24kgs |
| Noise Level (dB) | 40 dB |
| Certification | CSA/CE/FCC/ETL/WEEE/RoHS ISO 9001 and ISO 14001 certified |

Full Glass Door Options



Customized silkscreening available including logo's

Solid Laminated Door Options



* Measured to door handle

**Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature, in compliance with EN ISO 7371

† Recommended weight of panel is no more than 9 lbs. (4.08Kg). Recommended thickness, 3/4 inches (18-20mm)

Specifications may change without notice due to continuous product development.