

Non-Automated  
Minibars



THE  
**SMARTCUBE®**  
CLASSIC COLLECTION  
(non-automated)



MINIBAR SYSTEMS  
smart bars • smart people • smart solutions



Classic LP60T solid foam glass door

# SmartCube Classic - Engineered to upgrade in the future

SmartCube Classic minibars have been quality engineered with generous internal space, simple and stylish design, low energy consumption and silent thermoelectric cooling technology. It's a great value for your hotel.



Classic LP40T glass door



Classic LP40T solid door



Classic DC40T Drawer minibar

## Quality Engineered

- 30% more energy efficient over previous models
- Environmentally sustainable energy efficient cooling system
- Peltier Thermoelectric Superconductor 5 Heat Pipe technology
- State-of-the-art insulation properties (Argon, low-E glass)
- Solid foam insulated frame for glass door
- Magnetic seals to keep the door tightly closed
- Free of hazardous materials
- Cyclopentane foaming agent – most environmentally friendly material
- Automatic defrost

## Upgradable Design

- Classic Honor Bar -> Door Open -> Fully Automated
- Maximum Flexibility
- Customized front panel to integrate with design†
- Case good cabinet door sliders available

## Technical Specifications

	Classic LP40T	Classic LP60T	Classic DC40T
<b>Capacity (liters / cubic feet)</b>	40 / 1.41	50 / 1.766	40 / 1.41
<b>Dimensions HxWxD (inches)</b>	22.92 x 16.14 x 18.7*	22.92 x 19.29 x 18.7*	17.52 x 21.65 x 19.56††
<b>HxWxD (mm)</b>	582.4 x 410 x 475*	582.4 x 490 x 475*	445 x 550 x 497††
<b>Door Options</b>	Full Glass Front: No Window, Full Window, Partial Window, Stainless Full Window Solid Laminated: Black Solid, Stainless Steel		Full Glass Front: No Window Solid Laminated: Black Solid
<b>Door Hinge</b>	Reversible	Reversible	Drawer
<b>Shelves Type</b>	Tempered Glass	Tempered Glass	Metal
<b>Watts (W)</b>	60W	42-52W	40W
<b>Voltage (V)</b>	110V / 60Hz or 220V / 50Hz	110V / 60Hz or 220V / 50Hz	110V / 60Hz or 220V / 50Hz
<b>Amps</b>	0.5-0.9	0.35-0.75	0.35-0.75
<b>Consumption (kWh/24h)**</b>	0.43 kWh/24h**	0.32 kWh/24h**	0.32 kWh/24h**
<b>Net Weight (lbs / kgs)</b>	46.5 lbs / 21.1 kgs	52.91 lbs / 24 kgs	49.6 lbs / 22.5 kgs
<b>Noise Level (dB)</b>	40 dB	40 dB	40 dB
<b>Certification</b>	CCC/CB/CETL/CE/GS/RoHS/UL/CSA/ISO 9001 2008/ISO 14001 2004		

\* Measured to door handle

\*\* Average energy consumption per 24 hours, at 25°C (77°F) ambient temperature and 7°C (44.6°F) cooling temperature, in compliance with EN ISO 7371

† Recommended weight of panel is no more than 9 lbs. (4.08Kg). Recommended thickness, ¾ inches (18-20mm)

†† Depth with handle is 20.47 inches (520 mm). Handle adds 0.9 inches (23mm) to depth

Specifications may change without notice due to continuous product development.

## Sophisticated Finish

- Translucent racking on door for high visibility of products
- Internal LED lighting
- High impact exterior finish
- Full Glass Face Door Options: no, partial or full window
- Solid Laminated Door Options: black solid, stainless steel
- Custom: stainless steel full window

## Full Glass Door Options



## Solid Laminated Door Options

